



8403 Tanglerose Dr.
 Frisco, TX 75033
 Phone: (817) 905-8562
 www.cleartunin.com
 vsoto@cleartunin.com

CUSTOM HAMMER BORING ORDER FORM

Piano Specifications:

Make: _____
 Model: _____
 Year: _____

CUSTOMER INFORMATION:	HAMMER BORE SERVICES:
Name:	Bore To Samples Include the first and last hammer from each section. Leave hammerheads attached.
Address:	Bore To Specs See Below
City/State/Zip or Country:	Pre-File Tapered See Below
Phone:	Hang
Email:	Drill Size #: _____ (1) .1875" (2) .189" (3) .203 (4) .205" (5) .213" (6) .2165" (7) .2188" (8) .224" (9) .221"

BORE TO SPECS: All of the Information below is REQUIRED if hammer samples are not provided

Bore Distance: Bass _____mm, _____mm, Tenor _____mm, _____, Treble _____mm, _____, Treble _____mm, _____

Note: If bore distance is not provided then provide the following:

a) Keybed to String Distance: (Make sure to measure the **first** and **last** string per section)

Bass _____mm, _____mm, Tenor _____mm, _____, Treble _____mm, _____, Treble _____mm, _____, Treble _____mm, _____

b) Keybed to Centerpin Distance: _____mm

Tail Length: _____ mm

Rake: _____ (usually 90 deg.)

of Bass Hammers _____

Bass Bore Angle: _____deg.

Tenor and Treble Bore Angles:

Hammer #	Angle		Hammer #
_____	_____ deg	Tenor Section	_____
_____	_____ deg	(first, last)	_____, _____
_____	_____ deg	Treble Section	_____
_____	_____ deg	(first, last)	_____, _____
_____	_____ deg	Treble Section	_____
_____	_____ deg	(first, last)	_____, _____
_____	_____ deg		
_____	_____ deg		

Taper: 1 mm 1.5 mm 2 mm Hammer Width: _____ mm

Note: Standard taper removes 1mm off each side of the hammer

Cove: Standard C-Shape 3mm Custom: _____ mm

1 1/4" Radius 1 1/2" Radius

Note: Standard C-Shape cove has a 1 1/4" radius

Tail Shaping (also known as "Arc"): Standard

